



* Product not exactly as shown

Compact Inverter/Chargers to Power The Comforts of Home On Your RV or Truck

With modified sine wave output, Freedom HW 1000 Inverter/Charger is designed to run entertainment systems and small appliances while charging and providing DC power for battery banks in smaller RV's, and trucks. The Freedom HW Inverter/Charger is the smallest, lightest, and most versatile inverter/charger model in the Xantrex lineup.

The Freedom HW is available with 1000 watts inverter output and 55-amp charger and is designed to meet the demanding standards of RV and commercial vehicle manufacturers. Temperature-controlled multistage charging ensures that your batteries are recharged safely and efficiently. It includes a 30-amp automatic transfer switch and a detachable digital remote control panel display that provides precise system information and can be mounted wherever you require the information.

Product Features

- ▶ Designed to power demanding loads such as microwave ovens, TVs, DVD players, small appliances and other electronic equipment
- ▶ Removable digital display to provide system status
- ▶ Automatic three-stage battery charger
- ▶ Designed to be hardwired using a terminal strip
- ▶ Built-in 30-amp relay to automatically transfer between inverter power and incoming AC utility power
- ▶ KKK-A-1822D and UL458 compliant

Protection Features

- ▶ Battery over-voltage and under-voltage protection
- ▶ Over-temperature shutdown
- ▶ Automatic overload protection
- ▶ Short-circuit protection
- ▶ Ground-fault protection
- ▶ ETL listed for use in mobile RV and commercial applications

Xantrex Technology Inc.

Headquarters
8999 Nelson Way
Burnaby, British Columbia
Canada V5A 4B5
800 670 0707 Toll Free
604 420 1591 Fax

541 Roske Drive, Suite A
Elkhart, Indiana
USA 46516
800 446 6180 Toll Free
574 294 5989 Fax

www.xantrex.com

Freedom HW 1000 Inverter/Charger**Electrical Specifications - Inverter**

Models	HW 1000
Output power (continuous)	1000 W
Surge power	2000 W
Output frequency regulation	60 Hz
Inverter voltage regulation	115 +/-10 Vrms
Output wave form	Modified sine wave
Efficiency (full load)	> 82%
Peak efficiency	> 87%
No-load current draw (idle mode)	< 1 Adc
Off mode current draw (display off)	< 5 mA

Electrical Specifications - Charger

Charge rate	55 A
AC input voltage range	95 – 130 Vac
AC transfer relay	30 A
Battery voltage (nominal)	12 Vdc
Battery voltage range	10.5 – 15.5 Vdc
Low battery cut-out	10.5 Vdc
AC input (max. charge)	5 Aac
Default bulk charge voltage setting	14.2 Vdc
Default float charge voltage setting	13.5 Vdc
Equalize charge voltage (wet cell only)	N/A
Battery charge outputs	One
Charge control	Three-stage
Battery type settings	Flooded / Gel / AGM / Fixed 13.5 Vdc
Equalization	No
Internal temperature-sensitive charging	Yes

General Specifications

Optimal operating temperature range	32°F to 104°F (0°C to 40°C)
Optional remotes	Detachable display
Unit weight	10 lb (4.5 kg)
Unit dimensions (H x W x L)	4.2 x 9.5 x 15.5" (106 x 241 x 393 mm)
Warranty	One year
Part number	806-1055

Regulatory & Environmental Compliance

Certified to CSA Standard C22.2 No. 107.1, UL458 and KKK-A-1822D.